



**PRODUCTION INSTRUCTION OF PO - 1856 / AO-S E-12 / REVERSIBLE (LID)**

<b>DESCRIPTION</b>	<b>47*50</b>
<b>Party Quality</b>	<b>2200</b>
<b>Party Weight</b>	<b>.517</b>
<b>Production Quality</b>	<b>2212</b>
<b>Production Weight</b>	<b>.520</b>
<b>Pile Height - A</b>	<b>0</b>
<b>Pile Height - B</b>	<b>0</b>
<b>Pile Height - C</b>	<b>0</b>
<b>Stitching 10 Cm A</b>	<b>0</b>
<b>Stitching 10 Cm B</b>	<b>0</b>
<b>Stitching 10 Cm C</b>	<b>0</b>
<b>Width in Line 5 cms</b>	<b>0</b>
<b>Middle Gape / Weaving Com</b>	<b>0</b>
<b>1. Yarn UV/Non UV</b>	<b>UVC</b>
<b>2. Canvas UV/Non UV</b>	<b>70-UVC</b>
<b>3. Canvas Size</b>	<b>70</b>
<b>4. Canvas Quality</b>	<b>.650</b>
<b>5. Canvas Weight @ PC.</b>	<b>0</b>
<b>6. Canvas Cutting Size</b>	<b>0</b>
<b>7. Pipen Tanki Fold</b>	<b>AS PER SAMPLE</b>
<b>8. Stiching in 5 CMS</b>	<b>8-9</b>
<b>9. Pipen Folder MM</b>	<b>AS PER SAMPLE</b>
<b>10. Latex</b>	<b>NO</b>
<b>11. Export Packing</b>	<b>NO</b>

<b>12. Carving</b>	<b>NO</b>
<b>TUMBLER / WASHING</b>	<b>NO</b>
<b>PC DYEING WEIGHT</b>	<b>.505</b>
<b>PC WASHING WEIGHT</b>	<b>0</b>
<b>TUMBLING WEIGHT</b>	<b>0</b>
<b>TUFFTING FINAL WEIGHT</b>	<b>.490-.520</b>
<b>EXTRA WORK WEIGHT</b>	<b>0</b>
<b>ORDER QUANTITY</b>	<b>126</b>