



PRODUCTION INSTRUCTION OF PO - 2038 / AO-CCPL-4 / RT-17066 (REVERSIBLE)

DESCRIPTION	70*120	60*100	45*50	50*90	50*80
Party Quality	2200	2200	2200	2200	2200
Party Weight	1.321	1.321	1.321	1.321	1.321
Production Quality	2416	2416	2416	2416	2416
Production Weight	1.45	1.45	1.45	1.45	1.45
Pile Height - A	60-61	60-61	60-61	60-61	60-61
Pile Height - B	0	0	0	0	0
Pile Height - C	0	0	0	0	0
Stitching 10 Cm A	20-21	20-21	20-21	20-21	20-21
Stitching 10 Cm B	0	0	0	0	0
Stitching 10 Cm C	00	0	0	0	0
Width in Line 5 cms	10	10	10	10	10
Niddle Gape / Weaving Code	FULL GAPE	FULL GAPE	FULL GAPE	FULL GAPE	FULL GAPE
1. Yarn UV/Non UV	UVC	UVC	UVC	UVC	UVC
2. Canvas UV/Non UV	CANVAS 53 CANV 600	CANV 600	CANV 600	CANV 600	CANV 600
3. Canvas Size	53	53	53	53	53
4. Canvas Quality	600	600	600	600	600
5. Canvas Weight @ PC.	0.585	0.425	0.160	0.335	0.230
6. Canvas Cutting Size	73*132	63*110	48*55	43*99	53*88
7. Pipen Tanki Fold	AS PER	AS PER	AS PER	AS PER	AS PER
8. Stiching in 5 CMS	9	9	9	9	9
9. Pipen Folder MM	42	42	42	42	42
10. Latex	NO	NO	NO	NO	NO
11. Export Packing	NO	NO	NO	NO	NO

12. Carving	NO	NO	NO	NO	NO
TUMBLER / WASHING	NO	NO	NO	NO	NO
PC DYEING WEIGHT	2.00	1.430	0.540	1.065	0.965
PC WASHING WEIGHT	0	0	0	0	0
TUMBLING WEIGHT	0	0	0	0	0
TUFFTING FINAL WEIGHT	1.950-2.050	1.400-1.460	0.520-0.560	1.010-1.090	0.930-0.980
EXTRA WORK WEIGHT	0	0	0	0	0
ORDER QUANTITY	1020	1065	1660	1475	795